Version 1.1 02/08/2022

emulseo

Safety Data Sheet

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Fluo-ST1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Laboratory Chemical

1.3 Details of the supplier of the safety data sheet

Emulseo Cheminnov - 14 avenue Pey Berland 33600 Pessac France contact@emulseo.com

1.4 Emergency telephone number

In case of emergency: +33(0) 535 541 006

Section 2: Hazards identification

2.1 Classification of the substances or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies. Classification according to Directive 67/548/EEC or 1999/45/EC as amended This preparation is classified as dangerous according to Directive 1999/45/EC and its amendments. Classification Xn:R65, Xi:R38, N:R51-53 The full text for all R-phrases is displayed in section 16. Classification according to Regulation (EC) No 1272/2008 as amended Skin corrosion/irritation Category 2 H315 - Causes skin irritation. Health hazards H336 - May cause drowsiness or dizziness. Specific target organ toxicity - single Category 3 narcotic effects exposure H304 - May be fatal if swallowed and enters airways. Aspiration hazard Category 1 H411 - Toxic to aquatic life with long lasting effects. Hazardous to the aquatic environment, Category 2 long-term aquatic hazard **Environmental hazards** Hazard summary Physical hazards Not classified for physical hazards. Health hazards Irritating to skin. Harmful: may cause lung damage if swallowed. Occupational exposure to the substance or mixture may cause adverse health effects. Environmental hazards Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Specific hazards Vapours may cause drowsiness and dizziness. Direct contact with eves may cause temporary

Specific hazards Vapours may cause drowsiness and dizziness. Direct contact with eyes may cause temporary irritation. Swallowing of the liquid, or vomiting as a result, may result in aspiration into the lungs. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.

Main symptoms Vapours may cause drowsiness and dizziness. Symptoms include itching, burning, redness, and tearing of eyes. Prolonged or repeated contact may dry skin and cause irritation. Be aware that symptoms of chemical pneumonia (shortness of breath) may occur several hours after exposure.

2.2 Label elements

Label according to Regulation (EC) No. 1272/2008 as amended Contains: Distillates (petroleum), hydrotreated light Hazard pictograms



Signal word Danger

Hazard statements H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects. Precautionary statements

Prevention

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing mist or vapour.

P271 Use only outdoors or in a well-ventilated area.

P264 Wash thoroughly after handling.

P273 Avoid release to the environment.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P362 Take off contaminated clothing and wash before reuse.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

P391 Collect spillage.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Supplemental label information None.

2.3 Other hazards

Not a PBT or vPvB substance or mixture. Direct contact with eyes may cause temporary irritation. Swallowing or vomiting of the liquid may result in aspiration into the lungs. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.

Section 3: Composition

3.1 Substances

Not applicable - product is a mixture.

3.2 Mixtures

General information

Chemical name	%	CAS-No. / EC- No.	REACH Registration No.	INDEX No.	Notes
Distillates (petroleum,	60-100	64742-47-8	-	649-422-00-2	
hydrotreated light		265-149-8			
Classification:	DSD: X	n;R65, Xi;R38, N;R	851-53		
	CLP: As	sp. Tox. 1;H304, SI	kin Irrit. 2;H315, S	STOT SE 3;H336, A	quatic Chronic
	2;H411				

List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The full text for all R-phrases is displayed in section 16 of the SDS.

Section 4: First aid measures

General information Keep victim warm. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1 Description of the first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration or give oxygen by trained personnel.

Skin contact Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Use soap if available. Get medical attention if irritation develops or persists. Wash clothing separately before reuse.

Eye contact Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues.

Ingestion IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2 Most important symptoms and effects, both acute and delayed

Vapors may cause nausea, headache and/or dizziness. Symptoms include itching, burning, redness, and tearing of eyes. Prolonged or repeated contact may dry skin and cause irritation. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure.

4.3 Indication of any immediate medical attention and special treatments needed

Treat symptomatically.

Section 5: Firefight measures

General fire hazards This product is not flammable or combustible. The product is not flammable. Will burn if involved in a fire.

5.1 Extinguishing media

Suitable extinguishing media

Foam. Dry powder. Carbon dioxide (CO2). Water Spray or Fog Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from substances or mixture

During fire, gases hazardous to health may be formed.

5.3 Advice for fire fighters

Special protective equipment for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Special fire fighting procedures

Use water spray to cool unopened containers. Move containers from fire area if you can do so without risk.

Section 6: Accidental releases measures

6.1 Personal precautions, precaution equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Local authorities should be advised if significant spillages cannot be contained. Keep out of low areas. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unprotected personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2 Environmental precautions

Do not contaminate water.

6.3 Methods and materials for containment and clearing up

Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil etc) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4 References to other sections

For personal protection, see Section 8 of the SDS. For waste disposal, see Section 13 of the SDS.

Section 7: Handling and storage

7.1 Precautions for safe handling

Eliminate all sources of ignition. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Wear appropriate personal protective equipment. Avoid breathing mists or vapours. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Store in a cool place. Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Store away from incompatible materials (see section 10 of the SDS). Flammable Liquids; Hazard Class for Storage: 3.

7.3 Specific end uses

Rain/water repellant treatment for glass surfaces.

Section 8: Exposure controls/personal protection

8.1 Control parameters

Belgium. Exposure Limit Values. Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8)	TWA	200 mg/m3	Vapor.
Bulgaria. OELs. Regulation No 13 on protection	on of workers a	gainst risks of exp	osure to chemical
agents at work Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8)	TWA	300 mg/m3	
Denmark. Exposure Limit Values			
Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8)	TLV	1 mg/m3	Mist.
Finland. Workplace Exposure Limits			
Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8)	TWA	500 mg/m3	-
nany. DFG MAK List (advisory OELs). Commis mical Compounds in the Work Area (DFG) Components		vestigation of Heal Value	th Hazards of Form
	ssion for the Inv Type TWA	-	Form
mical Compounds in the Work Area (DFG) Components	Туре	Value	Form Vapor and aeroso
mical Compounds in the Work Area (DFG) Components Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8)	Type TWA	Value 140 mg/m3 20 ppm	Form Vapor and aeroso
mical Compounds in the Work Area (DFG) Components Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa	Type TWA fety of Workpla	Value 140 mg/m3 20 ppm	Form Vapor and aeroso
mical Compounds in the Work Area (DFG) Components Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8)	Type TWA	Value 140 mg/m3 20 ppm	Form Vapor and aeroso Vapor and aeroso
mical Compounds in the Work Area (DFG) <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa <u>Components</u> Distillates (petroleum), TWA 200 mg/m3	Type TWA fety of Workpla Type Ceiling	Value 140 mg/m3 20 ppm ces Value 5 mg/m3	Form Vapor and aeroso Vapor and aeroso Form
mical Compounds in the Work Area (DFG) <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iceland. OELs. Regulation 154/1999 on occup <u>Components</u>	Type TWA fety of Workpla Type Ceiling ational exposur Type	Value 140 mg/m3 20 ppm ces Value 5 mg/m3 re limits Value	Form Vapor and aeroso Vapor and aeroso Form
mical Compounds in the Work Area (DFG) <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iceland. OELs. Regulation 154/1999 on occup	Type TWA fety of Workpla Type Ceiling ational exposur	Value 140 mg/m3 20 ppm ces Value 5 mg/m3	Form Vapor and aeroso Vapor and aeroso Form Mist.
mical Compounds in the Work Area (DFG) <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iceland. OELs. Regulation 154/1999 on occup <u>Components</u> Distillates (petroleum), TWA 200 mg/m3	Type TWA fety of Workpla Type Ceiling ational exposur Type	Value 140 mg/m3 20 ppm ces Value 5 mg/m3 re limits Value	Form Vapor and aeroso Vapor and aeroso Form Mist. Form
mical Compounds in the Work Area (DFG) <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iceland. OELs. Regulation 154/1999 on occup <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Ireland. Occupational Exposure Limits Components	Type TWA fety of Workpla Type Ceiling ational exposur Type	Value 140 mg/m3 20 ppm ces Value 5 mg/m3 re limits Value	Form Vapor and aerosol Vapor and aerosol Form Mist. Form
mical Compounds in the Work Area (DFG) <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iceland. OELs. Regulation 154/1999 on occup <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Ireland. Occupational Exposure Limits	Type TWA fety of Workpla Type Ceiling ational exposur Type TWA	Value 140 mg/m3 20 ppm ces Value 5 mg/m3 re limits Value 1 mg/m3	Form Vapor and aeroso Vapor and aeroso Form Mist. Form Mist.
mical Compounds in the Work Area (DFG) <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iceland. OELs. Regulation 154/1999 on occup <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Ireland. Occupational Exposure Limits <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iteland. Occupational Exposure Limits <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Lithuania. OELs. Limit Values for Chemical Sa	Type TWA fety of Workpla Type Ceiling ational exposur Type TWA TWA	Value 140 mg/m3 20 ppm ces Value 5 mg/m3 re limits Value 1 mg/m3 Value 5 mg/m3	Form Vapor and aeroso Vapor and aeroso Form Mist. Form Mist.
mical Compounds in the Work Area (DFG) <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iceland. OELs. Regulation 154/1999 on occup <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Ireland. Occupational Exposure Limits <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Ireland. Occupational Exposure Limits <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Lithuania. OELs. Limit Values for Chemical Sa 23:2007)	Type TWA fety of Workpla Type Ceiling ational exposur Type TWA TWA	Value 140 mg/m3 20 ppm ces Value 5 mg/m3 re limits Value 1 mg/m3 Value 5 mg/m3	Form Vapor and aerosol Vapor and aerosol Form Mist. Form Inhalable fration.
mical Compounds in the Work Area (DFG) <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Hungary. OELs. Joint Decree on Chemical Sa <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iceland. OELs. Regulation 154/1999 on occup <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Ireland. Occupational Exposure Limits <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Iteland. Occupational Exposure Limits <u>Components</u> Distillates (petroleum), TWA 200 mg/m3 Vapor.hydrotreated light (CAS64742-47-8) Lithuania. OELs. Limit Values for Chemical Sa	Type TWA fety of Workpla Type Ceiling ational exposur Type TWA TWA	Value 140 mg/m3 20 ppm ces Value 5 mg/m3 re limits Value 1 mg/m3 Value 5 mg/m3	Form Vapor and aerosol Vapor and aerosol Form Mist. Form Mist. Form Inhalable fration.

TWA

350 mg/m3

Vapor.hydrotreated light (CAS64742-47-8)

Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3	TWA	5 mg/m3	Mist.
Vapor.hydrotreated light (CAS64742-47-8)			

Norway. Administrative Norms for Contaminants in the Workplace

Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3	TLV	275 mg/m3	-
Vapor.hydrotreated light (CAS64742-47-8)		1 mg/m3	Mist.
		40 ppm	

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3	STEL	300 mg/m3	-
Vapor.hydrotreated light (CAS64742-47-8)	TWA	100 mg/m3	

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3	STEL	10 mg/m3	Aerosol
Vapor.hydrotreated light (CAS64742-47-8)	TWA	5 mg/m3	Aerosol
Spain. Occupational Exposure Limits			
Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3	STEL	10 mg/m3	Mist.
Vapor.hydrotreated light (CAS64742-47-8)	TWA	5 mg/m3	Mist.
Sweden. Occupational Exposure Limit Values	i		
Components	Туре	Value	Form
Distillates (petroleum), TWA 200 mg/m3	STEL	500 mg/m3	-
Vapor.hydrotreated light (CAS64742-47-8)	TWA	350 mg/m3	-

Biological limit values

No biological exposure limits noted for the ingredient(s). **Recommended monitoring procedures** Follow standard monitoring procedures. **Derived no-effect level (DNEL)** Not available. **Predicted no effect concentrations (PNECs)** Not available.

8.2 Exposure controls

Appropriate engineering controls

Use explosion-proof equipment. Provide adequate general and local exhaust ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours. Provide eyewash station.

Individual protection measures, such as personal protective equipment General information

Use personal protective equipment as required. Keep working clothes separately. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection

Wear protective gloves. Nitrile gloves are recommended but be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

- Other

Wear suitable protective clothing. Full body suit and boots are recommended when handling large volumes or in emergency situations. Wear protective gloves.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with gas filter (type A2).

Thermal hazards Wear appropriate thermal protective clothing, when necessary. Hygiene measures Do not get in eyes. Avoid contact with skin. Do not get this material on clothing. When using, do not eat, drink or smoke. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practices. Environmental exposure controls Environmental manager must be informed of all major releases.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Physical state Liquid. Form Liquid. Colour Colourless. Odour Hydrocarbon-like. Odour threshold Not available. pH Not available. Melting point/freezing point -77 °C (-106,6 °F) Initial boiling point and boiling range 218 - 257 °C (424,4 - 494,6 °F) Flash point > 94,0 °C (> 201,2 °F) Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Flammability limit – lower (%) 0,6 Flammability limit – upper (%) 4,9 Vapour pressure Not available. Vapour density Not available. Relative density 0,791 @ 15,6 °C (60,08 °F) Solubility(ies) Not available. Partition coefficient (n-octanol/water) No data available. Auto-ignition temperature > 200 °C (> 392 °F) Decomposition temperature Not available. Viscosity Not available. Explosive properties Not available. Oxidizing properties Not available.

9.2 Other information

No relevant additional information available.

Section 10: Stability and reactivity

10.1 Reactivity

The product is stable and non reactive under normal conditions of use, storage and transport.

10.2 Chemical Stability

Stable at normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Contact with incompatible materials. Avoid high temperatures. Protect against direct sunlight.

10.5 Incompatible materials

Strong oxidizers, strong acids, and strong bases.

10.6 Hazardous decomposition products

Carbon oxides. Hydrogen chloride.

Section 11: Toxicology information

Information on likely routes of exposure

Inhalation Vapours may irritate throat and respiratory system and cause coughing. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May be fatal if swallowed and enters airways. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms Vapours may cause drowsiness and dizziness. Symptoms include itching, burning, redness, and tearing of eyes. Be aware that symptoms of chemical pneumonia (shortness of breath) may occur several hours after exposure.

11.1 Information on toxicological effects

Acute toxicity Vapours may cause drowsiness and dizziness. Prolonged or repeated contact may dry skin and cause irritation. Direct contact with eyes may cause temporary irritation. Harmful if swallowed, can enter lungs and cause damage. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Be aware that symptoms

of chemical pneumonia (shortness of breath) may occur several hours after exposure.

Mixture versus substance information Not available.

Other information Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue) and/or damage.

Section 12: Ecological information

12.1 Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2 Persistence and degradability

The product is not expected to be readily biodegradable.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

The product is insoluble in water. The product contains organic solvents which will evaporate easily from all surfaces.

12.5 Results of PBT and vPvB assement

Not a PBT or vPvB substance or mixture.

12.6 Other adverse effect

The product contains a substance which has a photochemical ozone creation potential.

Section 13: Disposal consideration

13.1 Waste treatment methods

Residual waste Dispose of in accordance with local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Residual vapours may explode on ignition; do not cut, drill, grind, or weld on or near this container.

EU waste code 16 03 05*

Waste codes should be assigned by the user based on the application for which the product was used. **Disposal methods/information** Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14: Transport information

ADR

14.1. UN number UN3082
14.2. UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light)
14.3. Transport hazard class(es)
Class 9
Subsidiary risk Label(s) 9
Hazard No. (ADR) 90
Tunnel restriction code E
14.4. Packing group III
14.5. Environmental hazards Yes
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number UN3082
14.2. UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light)
14.3. Transport hazard class(es)

Class 9 Subsidiary risk -Label(s) 9 14.4. Packing group III 14.5. Environmental hazards Yes 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. ADN 14.1. UN number UN3082 14.2. UN proper shipping name Environmentally Hazardous Liquid, N.o.s. (Distillates (petroleum), hydrotreated light) 14.3. Transport hazard class(es) Class 9 Subsidiary risk -Label(s) 9 14.4. Packing group III 14.5. Environmental hazards Yes 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. ΙΑΤΑ 14.1. UN number UN3082 14.2. UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (DISTILLATES (PETROLEUM), HYDROTREATED LIGHT) 14.3. Transport hazard class(es) Class 9 Subsidiary risk -Label(s) 9 14.4. Packing group III 14.5. Environmental hazards Yes ERG Code 9L 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safetyinstructions, SDS and emergency procedures before handling. IMDG 14.1. UN number UN3082 14.2. UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES (PETROLEUM), HYDROTREATED LIGHT) 14.3. Transport hazard class(es) Class 9 Subsidiary risk -Label(s) 9 14.4. Packing group III Marine pollutant Yes 14.5. Environmental hazards EmS F-A. S-F 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Read safetyinstructions, SDS and emergency procedures before handling. **14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** This substance/mixture is not intended to be transported in bulk.

General information The product is eligible for Limited Quantity exemption because its unit size meets the relevant thresholds. It may be eligible for Excepted Quantity exemption, dependant on quantity of units within the outer package.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the susbtances or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I Not listed. Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II Not listed. Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed. Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended Not listed. Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended Not listed. Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended Not listed. Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended Not listed. Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry Not listed. Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed. Authorisations Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended Not listed. **Restrictions on use** Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed. Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work Not listed. Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding Not listed. **Other EU regulations** Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances Not listed. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work Distillates (petroleum), hydrotreated light (CAS 64742-47-8) Directive 94/33/EC on the protection of young people at work Not listed. Other regulations The product has been classified according to the legislation in force. The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended and respective national laws implementing EC

directives.

National regulations Follow national regulation for work with chemical agents.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out.

Section 16: Other information

List of abbreviations DSD: Directive 67/548/EEC. CLP: Regulation No. 1272/2008. DNEL: Derived No-Effect Level. PNEC: Predicted No-Effect Concentration. References Not available. Information on evaluation method leading to the classification of mixture The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12. Full text of any statements or R-phrases and H-statements under Sections 2 to 15 R38 Irritating to skin. R51 Toxic to aquatic organisms. R53 May cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
Training information Not available.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Emulseo, and to recommend precautionary measures for the storage and handling of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.